



CAL TRANS TYPE III-BF

SINGLE METER SERVICE PEDESTAL
SINGLE AND THREE PHASE APPLICATIONS

TYPICAL APPLICATIONS INCLUDE PARKING LOT LIGHTING, HIGHWAY, STREET AND SIGN LIGHTING AND TRAFFIC SIGNAL CIRCUITS.

STANDARD FEATURES

- METER SOCKET WITH TEST BLOCKS 4 JAW
- UTILITY LANDING LUGS 250 KCMIL
- STANDARD VOLTAGE 120/240VAC 1 PHASE 3 WIRE
- CIRCUIT BREAKER INTERIOR COPPER BUS
- ALL METERED 12 CIRCUIT 100 OR 200 AMPS
- OR
- (2) 8 CIRCUIT 100 AMP, METERED AND UNMETERED
- CUTLER-HAMMER PLUG IN BREAKERS
- PHOTOELECTRIC SOCKET PROVIDED WITH UNMETERED CIRCUITS
- ACCOMMODATES 42 CIRCUIT INTERIOR MAXIMUM
- OR A BOLT-ON PANELBOARD 30 CIRCUIT MAXIMUM

SPECIFICATIONS

- * COMPLIES WITH EUSERC STANDARDS & DWG. 309
- * 12 GA. NEMA 3R CONSTRUCTION
- * POLYESTER POWDER-COATED FINISH
- EXCEEDS ASTM B-117 SPECIFICATIONS
- * FABRICATED FROM CORROSION-RESISTANT
- ZINC COATED STEEL
- * AVAILABLE IN STAINLESS STEEL

- * LIGHT GREEN COLOR NO. 14672 PER
- FEDERAL SPECIFICATIONS 595 -
- CUSTOM COLORS AVAILABLE
- * ALL FACTORY WIRING 600 VOLT RATED COPPER
- * ALL COMPONENTS UL LISTED
- * ALL EXTERIOR DOORS AND COVERS PADLOCKABLE
- * UTILITY COVERS SEALABLE