



STANDARD PEDESTAL OF MISSOURI DEPARTMENT OF TRANSPORTATION

SINGLE METER SERVICE PEDESTAL

TYPICAL APPLICATIONS INCLUDE PARKING LOT LIGHTING, HIGHWAY, STREET AND SIGN LIGHTING AND TRAFFIC SIGNAL CIRCUITS.

STANDARD FEATURES

- METER SOCKET 5th clip JAW ASSY
- UTILITY LANDING LUGS 250 KCMIL
- STANDARD VOLTAGE 120/240VAC 1 PHASE 3 WIRE
- CIRCUIT BREAKER INTERIOR COPPER BUS 12 CIRCUIT
- LIGHTNING ARRESTER AVAILABLE 650 VAC (OPTION)
- MERCURY RELAY AND TERMINAL BLOCK SIZED FOR EACH LIGHTING CIRCUIT AS REQUIRED
- DOOR STOP TO PREVENT CUSTOMER DOOR SWINGING CLOSED
- PHOTOELECTRIC SOCKET

SPECIFICATIONS

- * NEMA 3R CONSTRUCTION
- * .125 ALUMINUM NON-ANODIZED
- * OPTION 12 GA. STEEL
 - + POLYESTER POWDER-COATED FINISH EXCEEDS ASTM B-117 SPECIFICATIONS
 - + FABRICATED FROM CORROSION-RESISTANT ZINC COATED STEEL
 - + FOREST GREEN COLOR STANDARD CUSTOM COLORS AVAILABLE
- * ALL FACTORY WIRING 600 VOLT RATED COPPER
- * ALL COMPONENTS UL LISTED
- * ALL EXTERIOR DOORS AND COVERS PADLOCKABLE
- * UTILITY COVERS SEALABLE