



FRONT
BASE DETAIL

SINGLE METER SERVICE PEDESTAL

IDEAL FOR APPLICATIONS THAT REQUIRE
EXTRA SPACE FOR FACTORY OR
CONTRACTOR INSTALLED COMPONENTS

STANDARD FEATURES

METER SOCKETS WITH TEST BLOCKS 4 JAW
UTILITY LANDING LUGS 250 KCMIL
STANDARD VOLTAGE 120/240VAC 1 PHASE 3 WIRE

SPECIFICATIONS

- * COMPLIES WITH EUSERC STANDARDS & DWG. 308
- * NEMA 3R CONSTRUCTION
- * POLYESTER POWDER-COATED FINISH
EXCEEDS ASTM B-117 SPECIFICATIONS
- * FABRICATED FROM CORROSION-RESISTANT
ZINC COATED STEEL
- * AVAILABLE IN ALUMINUM & STAINLESS STEEL

- * LIGHT GREEN COLOR NO. 14672 PER
FEDERAL SPECIFICATIONS 595 -
- * ALL FACTORY WIRING 600 VOLT RATED COPPER
- * ALL COMPONENTS UL LISTED
- * ALL EXTERIOR DOORS AND COVERS PADLOCKABLE
- * UTILITY COVERS SEALABLE
- * AUXILIARY CABINETS AVAILABLE (20-IN. & 30-IN. WIDE)