



UNMETERED SERVICE PEDESTAL

TYPICAL APPLICATIONS INCLUDE
 TELEPHONE INTERCONNECT CABINET
 FIBEROPTICS AND
 UNMETERED STREET LIGHTING
 IRRIGATION CONTROL ENCLOSURE

STANDARD FEATURES

UTILITY LANDING LUGS 250 KCMIL
 STANDARD VOLTAGE 120/240VAC 1 PHASE 3 WIRE
 CIRCUIT BREAKER INTERIOR PER JOB SPECIFICATIONS
 DEADFRONT CONSTRUCTION AS REQUIRED

SPECIFICATIONS

- * NEMA 3R CONSTRUCTION
- * POLYESTER POWDER-COATED FINISH EXCEEDS ASTM B-117 SPECIFICATIONS
- * FABRICATED FROM CORROSION-RESISTANT ZINC COATED STEEL
- * AVAILABLE IN ALUMINUM & STAINLESS STEEL

- * LIGHT GREEN COLOR NO. 14672 PER FEDERAL SPECIFICATIONS 595 - CUSTOM COLORS AVAILABLE
- * ALL FACTORY WIRING 600 VOLT RATED COPPER
- * ALL COMPONENTS UL LISTED
- * ALL EXTERIOR DOORS AND COVERS PADLOCKABLE
- * UTILITY COVERS SEALABLE